

# INDUSTRIAL LIGHTING

## LED SMALL WALL PACKS

- Wall mount luminaire with a classic design
- Best suited for entrances, underpasses or anywhere controlled security lighting is required
- The tough die cast aluminum housing is moisture and dustproof
- High quality, long life LEDs
- 4KVAC surge protection included
- IP68 light engines with screw free structure
- IP67 drivers and waterproof connections
- Colour Temperature: 4000K • Colour: Bronze

XE769



**STANPRO**

Model No.	Mfg. No.	Voltage	Wattage	Lamp Output	Price /Each
XE769	WPS-LS1-W/40K	120-277 V	39 W	3605 Lumens	
XE771	WPS-LS1-H/40K	347 V	39 W	3624 Lumens	
XE770	WPS-LS2-W/40K	120-277 V	59 W	4720 Lumens	
XE772	WPS-LS2-H/40K	347 V	59 W	4745 Lumens	

## LED MINI WALL PACKS

- High performance multi-purpose luminaire
- Effectively diffuses and distributes the highly efficient LED output to maximize spread while minimizing wattage consumption
- Best suited for security lighting over entrances, stairwells and pedestrian areas
- Polycarbonate housing and lens
- Integrated photocell
- High quality, long life LEDs
- Estimated lifespan of 50,000 hours
- 4KVAC surge protection included
- Colour Temperature: 5000K
- Colour: Bronze

XE764



**STANPRO**

Model No.	Mfg. No.	Voltage	Wattage	Lamp Output	Price /Each
XE764	WPI-LS1-W/50K/P	120 V	13 W	770 Lumens	

## LED LARGE FLOOD LIGHTS

- Powerful energy conserving floodlight
- Best suited for general lighting of grounds, storage yards, car dealers, parking areas and as floodlighting for signs and building fronts
- Made of die cast housing with a glass lens
- High quality, long life LEDs
- Estimated lifespan of 50,000 hours
- Fully sealed and gasketed for both upward and downward aiming
- Tamper proof screws come standard • IP65 rated
- 4KVAC surge protection included
- Colour Temperature: 4700K • Colour: Bronze

XE787



**STANPRO**

Model No.	Mfg. No.	Description	Voltage	Wattage	Lamp Output	Price /Each
XE787	FLD-L0105N3-W/47K	Narrow Beam	120 - 277 V	105 W	5697 Lumens	
XE788	FLD-L0105N3-H/47K	Narrow Beam	347 V	105 W	5697 Lumens	
XE789	FLD-L0105N5-W/47K	Medium Beam	120 - 277 V	105 W	5361 Lumens	
XE790	FLD-L0105N5-H/47K	Medium Beam	347 V	105 W	5361 Lumens	
XE791	FLD-LS1N7-W/47K	Large Beam	120 - 277 V	102 W	6755 Lumens	
XE792	FLD-LS1N7-H/47K	Large Beam	347 V	102 W	6755 Lumens	
XE793	FLD-LS2N3-W/47K	Narrow Beam	120 - 277 V	186 - 188 W	13880 Lumens	
XE794	FLD-LS2N3-H/47K	Narrow Beam	347 V	186 - 188 W	13880 Lumens	
XE795	FLD-LS2N5-W/47K	Medium Beam	120 - 277 V	186 - 188 W	15264 Lumens	
XE796	FLD-LS2N5-H/47K	Medium Beam	347 V	186 - 188 W	15264 Lumens	
XE797	FLD-LS2N7-W/47K	Large Beam	120 - 277 V	186 - 188 W	14765 Lumens	
XE798	FLD-LS2N7-H/47K	Large Beam	347 V	186 - 188 W	14765 Lumens	

## HIGH BAY FLUORESCENT LUMINAIRES

- Best suited for high-ceiling warehouses as well as areas where uniform and efficient lighting is required
- Housing is made with 22-gauge rolled steel with enamel powder coating applied post-production
- Miro® 4 reflector has a high efficiency rating of 95%
- Comes standard with a set of hooks and can be installed with aircraft cables
- A 6 ft. white power cable is installed on the luminaire
- Easy ballast access from below
- Length: 50-1/4" • Lamp Type: T5HO
- Does not include fluorescent lamps



XE806

**STANPRO**

Model No.	Mfg. No.	Voltage	Wattage	Price /Each
<b>4 LAMPS</b>				
XE806	F1FB-4M4TSH054-W	120 - 277 V	54 W	
XE808	F1FB-4M4TSH054-H	347 V	54 W	
<b>6 LAMPS</b>				
XE807	F1FB-4M6TSH054-W	120 - 277 V	54 W	
XE809	F1FB-4M6TSH054-H	347 V	54 W	

## FLUORESCENT LIGHT FIXTURES

- Sealed against water and moisture for wet and damp locations
- Uniform gasketing is inserted around the entire housing, ensuring a complete seal
- Polycarbonate housing and lens that are corrosion resistant and will not rot or rust
- Multiple conduit knockouts in housing ends and top
- Reinforced plastic lens latch clips
- UV stabilized, high clarity lens with prismatic cut-off
- Sealed strain relief/cable gland kit included
- 2 lamps
- Length: 50-1/4"
- IP65 rated
- Does not include fluorescent lamps

XE810



**STANPRO**

Model No.	Mfg. No.	Voltage	Wattage	Lamp Type	Price /Each
XE810	VT4F2T5H0054-W	120 - 277 V	54 W	T5HO	
XE811	VT4F2T5H0054-H	347 V	54 W	T5HO	
XE812	VT4F2T8032-W	120 - 277 V	32 W	T8	
XE813	VT4F2T8032-H	347 V	32 W	T8	

## LED VAPOUR TIGHT LINEAR FIXTURES

- A luminaire ideal for a variety of industrial, commercial, vandal resistant and residential applications
- Can be installed inside or outside
- Lightweight, flexible and durable polycarbonate construction makes the luminaire vandal resistant and highly impact resistant
- The housing is sealed with a uniform gasket that blocks the ingress of moisture and dust and reinforced snap clips lock the luminaire together
- Multiple conduit knockouts in housing ends
- Sealed strain relief/cable gland kit included
- Length: 50-1/4" • Colour Temperature: 4000K
- IP65 rated



XE815

**STANPRO**

Model No.	Mfg. No.	Voltage	Wattage	Lamp Output	Price /Each
XE815	VT4-LS1-W/40K	120 - 277 V	40 W	3612 Lumens	
XE816	VT4-LS2-W/40K	120 - 277 V	54 W	4936 Lumens	
XE817	VT4-LS3-W/40K	120 - 277 V	75 W	6454 Lumens	

## STELLA EXIT SIGNS

- C860 approved
- Features 120/347 VAC dual input (hardwire) and universal DC; 6 - 24 VDC or self powered
- Uses 2 W LED board
- Long life LED light source
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

XB930



XB933



Model No.	Mfg. No.	Description	Dimensions				Price /Each
			W"	x	D"	x	
XB930	SLE-SP-L-R-U-M	Exit	12	x	2.25	x	7.5
XB933	SLS-L-R-U-M-UDC	Sortie	18.5	x	2.25	x	7.5

## STELLA RUNNING MAN EXIT SIGNS

- Feature 120/347 VAC dual input (hardwire), universal DC; 6-24 VDC or self-powered
- Running Man sign uses a 2 watt LED source
- Long life LED light source
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

Model No. XE661

Mfg. No. SL-RM-L-U-0LR-M (AC)

Price/Each \$



XE661



Model No. XE662

Mfg. No. SL-RM-SP-L-U-0LR-M (Self-powered)

Price/Each \$

Model No. XE663

Mfg. No. SL-RM-L-U-0LR-M-UDC (6-24 VDC)

Price/Each \$

## TEMPESTA™ LED EMERGENCY LUMINAIRES

- Uses two LED modules that are wired in parallel
- Will only illuminate during a power failure
- LEDs are rated for 100,000 hours at L70
- Input Voltage: 120 - 347 V
- Wattage: 17 W
- High quality corrosion, flame and vandal resistant polycarbonate housing
- Comes standard with a Ni-MH battery pack that provides a minimum of 30 minutes of emergency lighting
- IP65 Rating



Model No.	Mfg. No.	Description	Dimensions				Price /Each
			L"	x	W"	x	
XE874	TA-LED-EM-120-347V-S	Surface Mounted	17	x	6 1/2	x	3 1/2
XE875	TA-LED-EM-120-347V-R	Recessed	19 1/4	x	9 1/2	x	3 1/2
XE876	TA-LED-EM-120-347V-TB	T-Bar Mount	23 3/4	x	7 1/2	x	4

## STELLA COMBINATION SIGNS

- C860 approved
- LED EXIT and SORTIE models 120/347 VAC dual input (hard wire)
- Push button test switch
- Self-powered for minimum 30 minutes -6 VDC 36 W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9 W tungsten heads
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish



Model No.	Mfg. No.	Description	Price /Each
XB929	SLE-6-36-L-R-U-M-2SR/9W	Exit	
XB932	SLS-6-36-L-R-U-M-2SR/9W	Sortie	

### REPLACEMENT BULB

XB338	LP104	9 W Tungsten
-------	-------	--------------

## STELLA RUNNING MAN COMBO EXIT SIGNS

- Running Man models are supplied with 120/347 VAC dual input (hardwire)
- Push button test switch
- Self-powered for minimum 30 minutes - 6V DC 36W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9-watt tungsten heads
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Certified for sale in Canada by an accredited certification body



Model No. XE664

Mfg. No. SL-RM-6-36-L-U-0LR-M-2SR/9W

Price/Each \$



## ILLUMINA® BS100 SERIES IP66 VAPOR-TIGHT

- Lightweight, durable 100% corrosion, flame and vandal resistant polycarbonate construction
- Designed to be resilient, highly efficient and easy to install
- For ceiling, wall, suspension and pendant installations
- UV stabilized to reduce the yellowing index
- Liquid silicone memory retention gasket allows for installations in wet locations
- Incorporates a "dual concave" parabolic high-output, metallized reflector
- Also approved for through wiring application



Model No.	Mfg. No.	Volts	Price /Each
XC441	BS10048T8232AC120V	120	
XC442	BS10048T8232AC347V	347	

# EMERGENCY LIGHTS



## NOVA EMERGENCY LIGHTING UNITS

- 120/277/347 VAC input
- Push button test switch
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Solid state transfer charger
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9 W tungsten heads
- 20-gauge steel construction with baked powder coat white paint finish
- Pre-stamped universal mounting and keyhole slots
- Output 6 VDC or 12 VDC at rated wattage for 30 minutes
- Batteries included



XA440



XA439



XA190



Model No.	Mfg. No.	Replacement Batteries	Voltage Output	Watts Output			Price /Each
				1/2 hr.	1 hr.	2 hr.	
XA190	NV-636/2SR	XA604	6	36	18	9	
XA438	NV-650/2SR	XB921	6	50	25	17	12
XA439	NV-680/2SR	XA605	6	80	40	26	20
XA440*	NV1272/2SR	XA604	12	72	36	24	18
XA441*	NV12120/2SR	XA605	12	120	80	65	25
XA442*	NV12150/2SR	XA605	12	150	80	65	40
XA443*	NV12180/2SR	XB922	12	180	100	60	45
XA444**	NV12250/2SR	XB922	12	250	125	83	62
XA445	NV12360/2SR	XA606	12	360	180	120	90
REPLACEMENT BULB			Description				
XB338	LP104		9 W Tungsten				

\* Two batteries required

\*\* Three batteries required

## NEMA12 EMERGENCY LIGHTING UNITS

- NEMA12 rated – water and dust tight units
- 120/277/347 VAC input
- Push button test switch
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Solid state transfer charger
- Brownout and low voltage protection
- Two top mounted, high impact thermoplastic PAR36 9 W weatherproof heads
- 20-gauge steel housing in industrial grey fibreglass finish
- Pre-stamped mounting holes
- Output 6 V or 12 VDC at rated wattage for 30 minutes
- Batteries included



SEG853



Model No.	Mfg. No.	Replacement Batteries	Voltage	Watts Output			Price /Each
				1/2 hr.	1 hr.	2 hr.	
SEG853	LDT-636/2LR-9w	XA604	6 VDC	36	18	9	0
SEG854	LDT-680/2LR-9w	XA605	6 VDC	80	40	20	10
SEG855*	LDT-1272/2LR-9w	XA604	12 VDC	72	36	18	9
REPLACEMENT BULB			Description				
XB338	LP104		9 W Tungsten				

\* Two batteries required

## SEALED LEAD ACID BATTERIES



Model No.	Mfg. No.	Description	Price /Each
XA604	BA-6-5.0BB	6 V, 5 Ampere-Hour	
XA605	BA-6-12.0BB	6 V, 12 Ampere-Hour	
XA606	BA-12-32.0BB	12 V, 32 Ampere-Hour	
XB921	BA-6-7.2BB	6 V, 7.2 Ampere-Hour	
XB922	BA-12-7.2BB	12 V, 7.2 Ampere-Hour	



XB922



XA604

See page 870  
for Glow in  
the Dark Tape  
& Markers

