



## 8" DRILL PRESSES

- Spindle is supported by high quality ball bearings
- Switch located at the front of the machine for easy access
- Positive depth stop for quick and easy adjustment
- 45° tilting table for angular drilling
- Includes: 1/2" drill chuck and key



<b>Model No.</b>	<b>TM197</b>
<b>Mfg. No.</b>	KC-108C
<b>Chuck Size:</b>	1/2"
<b>Speeds:</b>	5 (620-3100 RPM)
<b>Table Size:</b>	6 1/2" x 6 1/2"
<b>Spindle Taper:</b>	#33 JT
<b>Motor:</b>	2.5 A, 1 phase, 60 Hz
<b>Voltage:</b>	110 V
<b>Dimensions:</b>	6 3/4" x 16 1/2" x 23"
<b>Weight:</b>	38 lbs.
<b>Price/Each</b>	\$

## 10" DRILL PRESSES W/LASER

- Dual intersecting adjustable laser guides
- Spindle is supported by high quality ball bearings
- Switch located at the front of the machine for easy access
- Positive depth stop for quick and easy adjustment
- 45° tilting table for angular drilling
- Includes: 1/2" drill chuck and key



<b>Model No.</b>	<b>TBW135</b>
<b>Mfg. No.</b>	KC-110C
<b>Chuck size:</b>	1/2"
<b>Speeds:</b>	5 (570-3050 RPM)
<b>Table size:</b>	7 3/4" x 7 3/4"
<b>Spindle Taper:</b>	#33 Jacobs
<b>Motor:</b>	3.2 A, 1 phase, 60 Hz
<b>Voltage:</b>	110 V
<b>Dimensions:</b>	11" L x 18 1/2" W x 29" H
<b>Weight:</b>	70 lbs.
<b>Price/Each</b>	\$

## 13" FLOOR DRILL PRESSES W/LASER

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduce vibrations
- Comes with non-slip rubber feed handles
- 45° tilting table for angular drilling
- Locking depth stop for accurate repetitive blind hole drilling
- Includes: 5/8" drill chuck, key and 4" vise
- Light socket incorporated into drill press head (standard light bulb not included)



<b>Model No.</b>	<b>TM209</b>
<b>Mfg. No.</b>	KC-116FC
<b>Chuck size:</b>	5/8"
<b>Max. distance chuck to table:</b>	24"
<b>Max. distance chuck to base:</b>	45 1/2"
<b>Table size:</b>	12 13/16"
<b>Speeds:</b>	16 (210-3670 RPM)
<b>Spindle Taper:</b>	#2 Morse
<b>Motor:</b>	7.5 A, 1 phase, 60 Hz
<b>Voltage:</b>	110 V
<b>Dimensions:</b>	12 13/16" L x 25" W x 63 1/2" H
<b>Weight:</b>	147 lbs.
<b>Price/Each</b>	\$

## 13" DRILL PRESSES W/LASER

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduces vibrations
- Comes with non-slip rubber feed handles
- 45° tilting table for angular drilling
- Locking depth stop for accurate repetitive blind hole drilling
- Includes: 5/8" drill chuck, key and 4" vise
- Light socket incorporated into drill press head (standard light bulb not included)



<b>Model No.</b>	<b>BV666</b>
<b>Mfg. No.</b>	KC-116C
<b>Chuck size:</b>	5/8"
<b>Max. distance chuck to table:</b>	13 3/4"
<b>Max. distance chuck to base:</b>	26"
<b>Table size:</b>	12 13/16"
<b>Speeds:</b>	16 (210-3670 RPM)
<b>Spindle Taper:</b>	#2 Morse
<b>Motor:</b>	7.5 A, 1 phase, 60 Hz
<b>Voltage:</b>	110 V
<b>Dimensions:</b>	12 13/16" L x 25" W x 42" H
<b>Weight:</b>	125 lbs.
<b>Price/Each</b>	\$

## 15" FLOOR DRILL PRESSES W/LASER

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduces vibrations
- Comes with non-slip rubber feed handles
- 45° tilting table for angular drilling
- Locking depth stop for accurate repetitive blind hole drilling
- Includes: 5/8" drill chuck, key and 4" vise
- Light socket incorporated into drill press head (standard light bulb not included)



<b>Model No.</b>	<b>TM211</b>
<b>Mfg. No.</b>	KC-117FC
<b>Chuck size:</b>	5/8"
<b>Max. distance chuck to table:</b>	23"
<b>Max. distance chuck to base:</b>	44 1/2"
<b>Table size:</b>	13 5/8"
<b>Speeds:</b>	16 (210-3670 RPM)
<b>Spindle Taper:</b>	#2 Morse
<b>Motor:</b>	10.5 A, 1 phase, 60 Hz
<b>Voltage:</b>	110 V
<b>Dimensions:</b>	13 5/8" L x 25" W x 63 1/2" H
<b>Weight:</b>	157 lbs.
<b>Price/Each</b>	\$

## 17" FLOOR DRILL PRESSES

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduces vibrations
- Comes with non-slip rubber feed handles
- Tilting table for angular drilling
- Light fixture incorporated into the head casting illuminates the work table (light bulb not included)
- Includes: 5/8" drill chuck and key



<b>Chuck size:</b>	5/8"
<b>Speeds:</b>	16 (240-3400 RPM)
<b>Table size:</b>	13 3/4"
<b>Spindle Taper:</b>	#2 Morse
<b>Motor:</b>	12 A @ 110 V, 6 A @ 220 V
	1 HP, 1 phase, 60 Hz
<b>Voltage:</b>	110 V/220 V
<b>Dimensions:</b>	13 3/4" L x 25" W x 64" H
<b>Weight:</b>	185 lbs.

### w/o Safety Guard

<b>Model No.</b>	<b>TM213</b>
<b>Mfg. No.</b>	KC-118FC
<b>Price/Each</b>	\$

### w/Safety Guard

<b>Model No.</b>	<b>TMA036</b>
<b>Mfg. No.</b>	KM-118FC-(LS)
<b>Price/Each</b>	\$

## 22" FLOOR DRILL PRESSES

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduce vibrations
- Tilting table for angular drilling
- Light fixture incorporated into the head casting illuminates the work table (light bulb not included)
- Comes with non-slip rubber feed handles



<b>Chuck size:</b>	3/4"
<b>Speeds:</b>	12 (150-4200 RPM)
<b>Table size:</b>	18 3/4" x 16 1/4"
<b>Spindle Taper:</b>	#4 Morse
<b>Motor:</b>	1 HP, 1 phase, 60 Hz
	12.5 A @ 110 V, 6.25 A @ 220 V
<b>Voltage:</b>	110/220 V
<b>Dimensions:</b>	18 3/4" L x 33" W x 69" H
<b>Weight:</b>	360 lbs.

### w/o Safety Guard

<b>Model No.</b>	<b>TM214</b>
<b>Mfg. No.</b>	KC-122FC
<b>Price/Each</b>	\$

### w/Safety Guard

<b>Model No.</b>	<b>TMA037</b>
<b>Mfg. No.</b>	KM-122FC-(LS)
<b>Price/Each</b>	\$

## 21" GEARHEAD DRILLING MACHINES

- 1.5 HP
- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Head tilts 90° to the left and 30° to the right
- Includes: 1/2" chuck with key, 3 1/2" angle vise and safety guard



<b>Model No.</b>	<b>TS208</b>
<b>Mfg. No.</b>	KC-40HS
<b>Chuck size:</b>	1/2"
<b>Speeds:</b>	6 (60-1500 RPM)
<b>Table size:</b>	21 3/4" x 19 1/2"
<b>Spindle Taper:</b>	#3 Morse
<b>Motor:</b>	1.5 HP, 11 A
<b>Voltage:</b>	220 V, 1 phase, 60 Hz
<b>Dimensions:</b>	21 1/4" L x 30" W x 78" H
<b>Weight:</b>	575 lbs.
<b>Price/Each</b>	\$

## DRILLING ACCESSORIES



Model No.	Mfg. No.	Description	Price /Each
<b>TJZ763</b>	KM-116	Drill press chuck safety guard for BV666 and TM209	
<b>TMA035</b>	KM-117	Drill press chuck safety guard for TS206 and TM211	
<b>TJZ764</b>	KM-118	Drill press chuck safety guard for TM213	
<b>TJZ765</b>	KM-122	Drill press chuck safety guard for TM214	

